

YC-395EL

Real Air Cooling

The multi-duct vortex refrigeration system and finned evaporator can prevent frosting completely and improve temperature uniformity to a large extent.

Real Energy Saving

The refrigerator is equipped with "M + Energy Core" power management system and complete air cooling design, improving energy saving efficiency by more than 40%.

MM Real Visibility

The electrical heating + LOW-E design with double considerations can achieve a better anti-condensation effect for the glass door.

Real Safety

Seven temperature probes can ensure high precision of temperature control with nearly no fluctuation and thus can improve safety.




Scope of Application

Suitable for storage of biological products, vaccines, drugs, reagents, etc. Suitable for use in pharmacies, pharmaceutical factories, hospitals, centers for disease prevention & control, clinics, etc.

Performance Data / Cooling Curve

Cooling Air Temp CC) 30 25 20 15 10 5 0 0 10 20 30 40 50 60 70 80 90 100 110 120 130 140 (min)

External Dimensions



2~8°C Pharmacy Refrigerator	
Model	YC-395EL
Cabinet Type	Upright
	395
Capacity(L)	595 580*533*1352
Internal Size(W*D*H)mm	
External Size(W*D*H)mm	650*673*1992
Package Size(W*D*H)mm	717*732*2065
NW/GW(Kgs)	95/111
Performance	0.000
Temperature Range	2~8°C
Ambient Temperature	16-32°C
Cooling Performance	5°C
Climate Class	N
Controller	Microprocessor
Display	Digital display
Refrigeration	
Compressor	1pc
Cooling Method	Air cooling
Defrost Mode	Automatic
Refrigerant	R600a
Insulation Thickness(mm)	R/L:35,B:52
Construction	
External Material	PCM
Inner Material	HIPS
Shelves	6+1(coated steel wired shelf)
Door Lock with Key	Yes
Lighting	LED
Access Port	1pc. Ø 25 mm
Casters	4+(2 leveling feet)
Data Logging/Interval/Recording Time	USB/Record every 10 minutes / 2 years
Door with Heater	Yes
Alarm	
Temperature	High/Low temperature, High ambient temperature
Electrical	Power failure , Low battery
Liectricat	
System	Sensor failure,Door ajar, Built-in USB datalogger failure,Condenser overheating
Electrical	
Power Supply(V/HZ)	220-240~/50
Power(W)	252
Power Consumption(KWh/24h)	3
Rated Current(A)	1.8
Accessories	
Options	Printer
Standard	RS485,Remote alarm contact,Backup battery
e model, parameters and performance specified in this brochure may be o	

^{*}The model, parameters and performance specified in this brochure may be changed without prior notice because of product upgrading.

*There may be differences between the product images shown in this brochure and the actual products. When you are buying any product, please check the actual product.

